



M&M PROTEK
since 2005

Ficha Técnica

Sapato EAGLE
EN ISO 20345:2011 S3
Ref. SFPS2781306



Descrição:

- Sapato segurança com atacadores, multi-funcional, especialmente leve e confortável;
- Gáspea preta com uma espessura de 1,8 a 2,0 mm
- Cordura preta;
- **Materiais forro:** têxtil 3D excelentes características de absorção de humidade, permite a circulação do ar;
- **Pala e gola:** almofadados e macios, para um maior conforto;
- **Palmilha de conforto:** em poliuretano expandido -Amovível;
- **Sola:** em poliuretano de dupla densidade com suporte lateral e reforço na biqueira; Excelentes características de amortecimento; Boa adesão em qualquer tipo de superfície;
- **Biqueira protecção:** em compósito, resistente a 200 joules, 100% isenta de metal, anatómica e não condutivo, até 50% mais leve que comum biqueira de aço;
- **Palmilha protecção:** Têxtil não metálica, Protege 100% da planta do pé, mais leve e flexível, com isolamento térmico, maior sensibilidade e controlo do pé;

Peso:

Aproximadamente 480 gramas por pé no tamanho 36;

Tamanhos:

-35 ao 48

Largura:

-11;

Sola:

-SRC

Normas:

EN ISO 20345:2011 S3

EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/2689/161/05/19/1590 EXT 01/05/19

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : Parvez Shoes Pvt Ltd.
150 Feet Road, Jajmau – Kanpur 208010 (U.P.)
INDIA

Description

PPE Type : *a safety footwear*

Product reference : EAGLE S3 (PSL- 2781306)

Article code :

Construction and material of outsole : Injection, PU/PU

Pictures :



Reference standard : EN ISO 20345 : 2011

Classification : I

Size range : 36-48

Toecap nature : Non Metallic

Category : S3 SRC

Slip resistance : SRC

Insert nature : Non Metallic

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from MAY 2019

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

Issued in Lyon by

Maxence DREVET

Project Certification Manager

Date of first issue : 20 May 2019

End of validity date : 20 May 2024



Original CTC



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 98775649726

Parvez Shoes Pvt Ltd.

MANUFACTURER'S TECHNICAL FILE

Reference of the product : EAGLE S3 (PSL- 2781306)

Article code :

Technical file index : 01

Last update : MAY 2019

IDENTIFICATION

Reference of the product : EAGLE S3 (PSL- 2781306)
Article Code :
Minor variant of model : BUFFALO S3 (PSL-2781307)
Technical file index : 01
Last update : MAY 2019

Manufacturer :

Parvez Shoes Pvt Ltd.

150 Feet Road, Jajmau – Kanpur 208010 (U.P.)

INDIA

tel : +91 512-2461130

fax :

Factory :

Parvez Shoes Pvt Ltd.

150 Feet Road, Jajmau – Kanpur 208010 (U.P.)

INDIA

Tel : +91 512-2461130

FOOTWEAR DESCRIPTION

Footwear description:

The classification of this footwear is: I : Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear

The design of this footwear is: A : low shoe

Visual description:

General view :



Outsole view :



Reference of the mould : PUNA/GOA

Range of sizes :

36-48

Construction and material of outsole :

Injection, PU/PU

Field of use

automobile industry, Toy industry, construction industry, ware housing.

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input checked="" type="checkbox"/> Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input type="checkbox"/> Marking
§2.2	PPE is designed and manufactured in a way that perspiration resulting from use is minimised. Otherwise it must be equipped with means of absorbing perspiration.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input type="checkbox"/> Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input checked="" type="checkbox"/> Marking
§2.6	PPE is intended for use in potentially explosive atmospheres	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input checked="" type="checkbox"/> Marking
§2.9	PPE incorporating components which can be adjusted or removed by the user	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input type="checkbox"/> Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input checked="" type="checkbox"/> Marking
§2.14	Multi-risk PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input checked="" type="checkbox"/> Marking
§3.1.1	The PPE is intended to protect against impact caused by falling or ejected objects and collisions of parts of the body with an obstacle	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input checked="" type="checkbox"/> Marking
§3.1.2.1	The PPE is intended to protect against falls due to slipping	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input checked="" type="checkbox"/> Marking
§3.2	The PPE is intended to protect against static compression of a part of the body	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input checked="" type="checkbox"/> Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard
			<input checked="" type="checkbox"/> Instruction for use
			<input checked="" type="checkbox"/> Marking

FOOTWEAR CONSTITUTION

	Ref	Material	Color
UPPER	U2	Cow Split Barton Din 2.0-2.2mm	Black
COLLAR	501555	PU Crispy	Black
	501555	PU Crispy BACKING	Grey
TONGUE	501555	PU Crispy	Black
	501555	PU Crispy BACKING	Grey
VAMP LINING	500385	Non woven	Grey
QUARTER LINING	500352	quarter lining: Synthetic Lining spacer	Silver
	Q2	seat region lining/ heel grip: Micro Fiber Suede 1.2 mm (polyurethane)	Black
INSOCK	IN 1	EVA and woven perforated	Black/grey
OUTSOLE	PUNA/GOA	PU/PU	Black/grey
INSOLE	INS 1	Q Flex TX T6 - Kevlar	Black and White
TOE CAP	004 Paradium Composite	Composite toecap	Off white
INSERT	INS 1	Q Flex TX T6 - Kevlar	Black and White
DECORATIVE ELEMENTS		METAL EYELET	BLACK

PROTECTION SCOPE

Basic requirements :

This product has been designed to be a safety footwear.

The technical rules are :

European Standard EN ISO 20344 : 2011 Personal protective equipment - test methods for footwear

European Standard EN ISO 20345 : 2011 : Personal protective equipment - Safety footwear

It is a category II product

Requirement of the standard EN ISO 20345 : 2011 concerning the value of the coefficient of friction of ceramic tiles floor with detergent solution and steel floor with glycerol (SRC)

Requirement of the paragraph 5.8.1. Design of the standard EN ISO 20345 : 2011 concerning cleated outsole.

At the date of certificate, the product is in compliance with Annex XVII of European REACH regulation (n° 1907/2006 and revisions)

Additional requirements :

The additional requirements are :

- Closed seat region
- Antistatic footwear
- Energy absorption of seat region
- Fuel oil resistance
- Upper : Water penetration and water absorption
- Penetration resistance

MARKING - PACKAGING

Information printed on the footwear :

- * Logo of the authorized representative
- * Logo **CE**
- * Manufacturer's type designation
- * Postal address of manufacturer
- * Footwear's reference EAGLE S3 (PSL- 2781306)
- * Article code
- * Size
- * Year of manufacture and at least quarter
- * The number and year of the Standard used
- * The symbol(s) of the additional requirements

Marking example :



The location of marking is : tongue

Method of marking on the footwear :

Stitch

Packaging :

10 PAIRS IN A CARTON

References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	References	Laboratory	References
FDDI	2K1501258	CTC	I161002142R
FDDI	2K1611183	CTC	I170200473R2
FDDI	2K1705124-2/CL	CTC	I170401015R
FDDI	2K1705124-B	CTC	I170401016
FDDI	2K1810083-A		
FDDI	2K1810083-B		
FDDI	2K1812079-A		
CTC	D181019898_1		
CTC	D181019900_1		
CTC	D181223699_1		
CTC	D181223701_1		
INTERTEK	GZHT90680526		

MEANS OF CONTROL

The core material for Safety Shoes is a Leather which is self-produced in our sister concern unit Indian Tanning Industries which produce leather as per the Instructions provided to maintain the quality and the technical specification as per the customer's requirement. Our most experienced person from Production Department selects the leather and then we start with cutting of the leather after the component cutting they are passed by the QC department and then they are transferred to Stitching department where the upper get closed and during the stitching they are inspected by Line man after that by the quality inspector, after the inspection it is transferred to metal fixing department and then to Strobel block and after that to Lasting department where tested Steel Toe are fixed with uppers after that the lasted upper go through the QC depart and the it is transfer to Injection unit for which we buy Imported PU chemicals during the soling process the shoes are inspected online and after that it is sent to finishing and packing depart at last the most talented passer inspect the complete shoes and after that it is moved to boxes and carton where the Shoe are ready for dispatch.

Samples are selected from different lots and send them for home lab to ensure that it fulfills customer's requirement and time to time to official testing bodies just to ensure that quality is up to the EN standards. pertinent tests & frequency: we will pick up 10 pairs safety shoes randomly from each batch and test slip resistance, antistatic and outsole flex according to EN ISO 20345:2011.

PPE subject to ageing :

Peremption period : 2 years when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear, ...).

Declaration of conformity :

Available with product.